



ENTERO SQ-M X TW 96518 B

28545 9010 B



AVAILABLE IN

BLACK 28545 9010 B

FLEMISH BRONZE OUTDOOR 28545 9010 FBRX

ANTHRACITE (DARK GREY) 28545 9010 N

WHITE 28545 9010 W



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 92 x 92
RECESSED DEPTH (MM)	140
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.465
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	661lm // 10W // 64lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

ENTERO SQ-M X TW 96518 B




28545 9010 B

Accessories

- ENTERO M HONEYCOMB
- ENTERO M LINEAR SPREAD LENS
- ENTERO M SPREAD LENS
- ENTERO M SOFTENING LENS
- ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28545_XXXO_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-


ENTERO SQ-M X TW 96518 B

28545 9010 B

FINISH YOUR SPECIFICATION

LED power supplies


#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2


Light altering devices




28500 0070 ENTERO M LINEAR SPREAD LENS




28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS



28500 0100 ENTERO M GLASS SBL



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

Notes: