



ENTERO RD-L TRIMLESS 92730 B



28435 9220 B

AVAILABLE IN

BLACK 28435 9220 B

GOLD COLOURED 28435 9220 GC

WHITE 28435 9220 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350-1050mA-DC Optional REFLECTORS 18° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-36,5W / CRI>90 (R9: 60) / 2700K / 1561-4380lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	4380lm // 36,5W // 120lm/W
LED TECHNICS (LUMINAIRE)	3479lm // 42W // 83lm/W

Remarks

Max.900mA when using 1 accessory; max 800mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO ROUND L
LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM

ENTERO RD-L TRIMLESS 92730 B


















28435 9220 B

Accessories

ENTERO L HONEYCOMB
 ENTERO L LINEAR SPREAD LENS
 ENTERO L SPREAD LENS
 ENTERO L SOFTENING LENS
 ENTERO L GLASS SBL

For detailed installation instructions, please consult the manual: [28435_XXXO_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT ENTERO RD-L	Required
 Plasterboard	 MOUNTING KIT ENTERO RD-L	Required
 Stucanet	 MOUNTING KIT ENTERO RD-L	Required
 Wood	 MOUNTING KIT ENTERO RD-L	Required
 Concrete + plaster	 MOUNTING KIT ENTERO RD-L	Required
 Lintel + plaster	 MOUNTING KIT ENTERO RD-L	Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO RD-L	Required
 Stretched ceiling	 MOUNTING KIT ENTERO RD-L CSC	Required
	 MOUNTING KIT ENTERO RD-L WSC	Required


ENTERO RD-L TRIMLESS 92730 B

28435 9220 B

FINISH YOUR SPECIFICATION


LED power supplies

#




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

1(1)




300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9

1(1)




21012 0010 LED POWER SUPPLY MULTI POWER

1




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

1



21012 0035 LED POWER SUPPLY MULTI POWER DIM5


1



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1

Mounting kits




28400 0030 MOUNTING KIT ENTERO RD-L

ENTERO RD-L TRIMLESS 92730 B

28435 9220 B

Mounting kits stretched ceiling




28400 0090 MOUNTING KIT ENTERO RD-L CSC



28400 0150 MOUNTING KIT ENTERO RD-L WSC


Light altering devices




28500 0130 ENTERO L LINEAR SPREAD LENS




28500 0140 ENTERO L SPREAD LENS




28500 0150 ENTERO L SOFTENING LENS



28500 0160 ENTERO L GLASS SBL



28500 0170 B ENTERO L HONEYCOMB SINGLE USE B



28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B



ENTERO RD-L TRIMLESS 92730 B

28435 9220 B

Notes: